



Specifications Ledvance LED  
Downlight Comfort Dali UGR19  
Aluminium 42W/36W/30W  
5000lm/4200lm/3600lm 100D -  
930-940 CCT | Cutout 250mm - IP44 -  
Best Colour Rendering - Dali  
Dimmable

[View Product](#)

## General Information

|                          |                                         |
|--------------------------|-----------------------------------------|
| SKU                      | 255007                                  |
| EAN                      | 4099854491184                           |
| manufacturer_code        | 4099854491184                           |
| Brand                    | Ledvance                                |
| Manufacturer Name        | DL CMFT DA D250 P 42W MS 940 U19 WTLEDV |
| Any Lamp all-in warranty | 5 Years                                 |
| Average Lifetime (h)     | 100000                                  |

## Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Emergency Lighting          | No Emergency Unit  |
| Tiltable                    | No                 |
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 2x26               |
| Wattage                     | 42W                |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 930 Warm White     |
| Colour temperature (Kelvin) | 3000 Warm White    |
| Colour Rendering (Ra)       | 90-99              |

|                       |                                |
|-----------------------|--------------------------------|
| Colour of Light       | White                          |
| Light Colour Options  | Single Color                   |
| Beam Angle (degree)   | 55                             |
| Luminous Flux (Lumen) | 5000lm                         |
| Lumen per watt        | 119                            |
| Power factor          | >0.90                          |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | Opal                           |
| Product Type Category | LED Downlight                  |

## Fixture Information

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Recessed               |
| Cut out (mm)           | 250                    |
| IP-Rating              | IP44                   |
| Impact Protection (IK) | IK03 - 0.35 joule      |
| Operating Temperature  | -20 to +40             |
| Housing                | Aluminium              |
| Colour of the Fixture  | White                  |
| Fixture Connection     | PI [Push-in connector] |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 124 |
| Diameter (mm) | 265 |

 **Sensor Information** Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



**Up to 7 years warranty**

No Sensor

 **Easy** return process